

PLATINA WEATHERCOAT
LONG LIFE
 EXTERIOR EMULSION WITH PU



Colour Range



Over 2,000 shades

Finish



High Sheen

Toxicity



Fire Hazard Class

Non- flammable

Unusual Fire & Explosion Hazards

Material can splatter above 212°F.
 Polymer film can burn.



Pot Life of Thinned Material

Within 24 hrs.

Warranty *



Product Description

WeatherCoat Long Life is a premium exterior emulsion paint with PU and Silicon technology. The paint is designed for heavy rainfall areas and provides excellent protection against extreme rain and growth of fungus & algae. The PU component of the paint imparts durability along with high sheen to the paint film.

Recommended Use

Exterior plastered surfaces, concrete blocks and asbestos

Coverage

60 -70 sq.ft/ lt/2 coats, under ideal test conditions.

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/plastered surfaces – WeatherCoat Exterior Primer

Putty: For wall/plastered surfaces – Bison Wall Putty

Drying Time



SD: 30 min depending on weather conditions
 HD: 4-6 hours

Dilution Ratio



40% by volume
 For dark shades: 0-10%

Application Method



Brush/ Roller/ Spray

Gloss Level



12-16 at 60° GH when released

PLATINA WEATHERCOAT LONG LIFE

EXTERIOR EMULSION WITH PU



Packs



20 Ltr

Surface Preparation



For fresh/new surfaces: The surface should be allowed to cure properly.

Apply 1 coat of Illusion Sealer to avoid the problem of salt petering.



For Previously Painted Surfaces:



Strip all the old paint and remove all the loose dust, grease, fungus and algae by sanding or wire brushing.

Cracks, holes, dents and damp areas should be repaired properly before painting.



Treat the surface with Bio-wash solution and wash it next day with potable water. Leave the surface to dry thoroughly.

Health & Safety

If the paint comes in contact with eyes or skin, flush with a large amount of water for at least 15 minutes. See a physician, if irritation persists. Wash affected skin areas with soap and water.

Priming: Apply 1-2 coats of Seal-O-Prime. For best results apply WeatherCoat Elastomeric Primer.

Directions for Application

Apply 2-3 coats of topcoat keeping an interval of 4-6 hours between each coat.

Points to Note

- ▶ Shake well before use and do not over dilute or over extend brush
- ▶ Stir and strain the material through a fine sieve before use
- ▶ Do not apply on high alkaline surface
- ▶ Do not apply paint on a wet surface
- ▶ Do not apply paint on chalking or flaking surface or where the surface is infected with fungus / algae
- ▶ Do not apply paint if the ambient temperature is less than or expected to fall below 10° C
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Version No: BPP1/05/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com