

DUROCEM EXTRA

Waterproof Cement Coating



USP

Value for Money



Excellent Hiding



Superior Adhesion



Excellent Brushability



IS Approved



Best In Class



Product Description

Berger Durocem Extra is a unique Product with Combination of Beauty, Durability and Affordability. It is manufactured with White Cement, Pigments, Extenders, and few additives which provides Hard, Durable and Treated film.


Usage Area

On exterior and interior plastered surfaces.

Recommended Surface

Sand/ cement plaster, surface, asbestos, brickwork, concrete block, etc.

Shade Range



Available in 20 direct shades

VOC (gm/ltr)



NA

Recommended Thinner



Potable water

Dilution Ratio



100% by volume

Consistency



Available in powder form

Drying Time



SD: 25 minutes to 30 minutes depending on weather conditions
HD: Overnight

Method of Application



Brush

Coverage



All in 1 coat primed surface

No. of coats

New Surface

Brush Application

1 coat

50-55 sq ft/kg/coat

*It depends on many conditions like surface conditions, surface preparation, application skill, dilution, painting specifications, etc. The above figures are on ideal laboratory conditions only and will vary depending on site conditions.

DUROCEM EXTRA

Waterproof Cement Coating



Packs



25kg

Pot life of Thinned Material



5-6 hrs

Certification: IS 5410

Safety Data: Refer MSDS

DIRECTIONS FOR USE

Surface Preparation



Remove all loose, flaky, chalky substances from the wall by wire brushing, water jetting (if required) or by using Berger sand / emery paper 180. Clean the surface with water and allow the surface to dry.

Dilution



1:1 by weight (Powder:Water). Add water and mix thoroughly using mechanical stirrer to get uniform consistency. Allow the mixture to stand for at least 10 min prior to application.

APPLICATION PROCEDURE



Pre-wet the wall surface with clean water before application of the 1st coat and wait for 30 min. This is highly recommended.



Apply coat of Durocem Extra using brush / spray and leave the surface to dry for 12-15 hrs.



Pre-wet the surface before application of 2nd coat and wait for 30 min.



Apply the second coat using brush / spray and leave it to dry overnight.



For proper curing spray clean water on the painted surface twice a day in hot weather for 2-3 days.

Special Note:

Before painting the following things should be checked thoroughly:

1. Moisture content of the wall (Ideal condition - below 12%)
2. pH value of the wall surface (Ideal condition-between 7-11)

If these are violated, owner will be responsible.

*As per test conducted at Berger R&D

Points to Note:

- Stir well before use and do not over dilute
- Proper surface preparation required
- Scrape off all old paint thoroughly before painting starts
- Strain the paint through clean cloth before application Keep the container tightly closed to prevent drying
- Please keep out of reach of children and away from foodstuff
- In case of contact with eyes, wash immediately with water and seek medical advice
- Use 1 or 2 coats of Bio-Wash for killing fungal growth
- For deeper shade apply 1 additional coat
- Don't apply paint on lime washed surfaces or damp wall
- Don't apply paint when ambient temperature is below 10°C or above 45°C
- Wear safety goggles and gloves
- Store the product in ambient condition, in a well-ventilated store
- Keep away from children, fire, etc.
- Avoid eye and skin contact. In case that happens, seek medical attention immediately

Version No: BPP1/03/2023. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
 Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com