

WALMASTA GLOW



Product Attributes



Sheen Finish
Imparts sheen finish to the walls

Resistant to Chalking & Fading



Prevents Fungi & Algae

Green Pro Certified
Validates our effort in striving towards cleaner, more sustainable future



Product Description

Walस्ता Glow is a modified acrylic emulsion based exterior paint suitable for moderate to dry climatic regions. The paint has higher sheen compared to economy paints, therefore imparts rich look on the exterior walls. The product is resistant to chalking, flaking, fading as well as prevents the growth of algae and fungi.

Recommended Use

Sand/cement plaster, asbestos, brickwork and concrete blocks
Note Not recommended on lime wash

Colour Range



Over 2,000 shades

Finish

- HIGH
- MEDIUM
- SMOOTH
- SOFT SHEEN ✓

Soft sheen finish

Toxicity



VOC <50 gm/lit
No added Lead, Arsenic, Chromium (VI) and Mercury

Recommended Undercoats

Primer: For wall/ plastered surfaces – HS Seal – O- Prime or WC Exterior Primer

Drying Time



SD: 30 minutes
(depending on weather conditions)
HD: 4 - 6 hours

Dilution



50 - 60% by volume with water
For darker shades: 0 - 10%

Recommended Thinner



Potable water

Gloss Level



3 - 6 at 60 ° GH (depends on shade)
measured as per standard method

Over Coating Interval



4 - 6 hours

Coverage



Approx. 50 - 60 sq.ft/ Lt/2 coats,
under ideal test conditions.
(Actual coverage may vary depending upon surface conditions, preparation and type of shade)

Application Method



Brush/ Roller/ Spray

WALMASTA GLOW



Packs



Fire Hazard Class
Non- flammable



Pot Life of Thinned Material
Use within 24 hours

Surface Preparation

For New Masonry surfaces



The surface should be allowed to cure completely.
Apply one coat of Illusion Sealer to avoid salt petering.

For Previously Painted Surfaces



Ensure the surface is free from all loose paints, dust particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe or scrub it clean by wire brushing.



Cracks, holes, dents or damp areas should be repaired properly before painting.



If required, treat the surface with Bio-wash solution, and wash it next day with potable water and let the surface to dry completely.

Priming:



Apply 1- 2 coats of HS Seal-O-Prime or WC Exterior Primer.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply 2-3 coats of Walmasta Glow topcoat paint with 4 – 6 hours of interval.

PRECAUTIONS

- Stir well and strain the diluted paint before use
- Do not over dilute or over extend brush
- Do not apply paint on high alkaline surface (pH of wall should be below 12)
- Do not apply paint on wet surface (moisture content of wall should be below 12%)
- Do not apply paint on chalking or flaking surface or where the surface is infected with fungus and algae
- Do not apply paint if the ambient temperature is less than or expected to fall below 10° C
- Use only Berger Paints machine colourants to tint shades
- Allow sufficient time for each coat to dry before next coat application
- Primer or one coat of paint should not be left exposed. Ensure complete application of process

Version No: BPP1/09/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com