Material Safety Data Sheet



Ruff 'N' Tuff - Decora Roller Coat

Durable Spike Textured Finish

Published Date: 10.05.2018

Seatton - 1

Product and Company Identification

Product Name: Ruff'N' Tuff - Decora Roller Coat

MFD & MKTD BY: BERGER PAINTS INDIA LTD.,

Berger House, 129 Park Street, Kolkata,

West Bengal, India - 700017

Phone 1800-103-6030 Email consumerfeedback@bergerindia.com

Seafon - 2

Composition / Information on Ingredients

Solid % - 76.50 \pm 2, Volatile % - 23.5.0 \pm 2, Emulsion Type – Modified Styrene Acrylic

Seatlon-3

Hazards identification

Not classified as hazardous according to regulatory criteria

Section - 4

First Aid Measures

• **Inhalation** : Move to fresh air.

• **Skin Contact**: Wash with water and soap as a precaution. If skin irritation persists, consult Doctor.

• **Eye contact** : Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion : Drink 1 or 2 glasses of water. Consult a physician if necessary. Never gives anything by mouth to an

Unconscious person.

Section - 5

Fire - Fighting Measures

- **Thermal decomposition:** Thermal decomposition may yield inorganic flakes or ash.
- Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.
- Specific hazards during firefighting: Material can splatter above 100°C/212°F. Dried product can burn.
- Special protective equipment for fire-fighters: Wear & use standard & protective apparatus.

Section - 6

Accidental Release Measures

- Personal precautions: Keep people away from & upwind of spill / leak. Material can create slippery conditions.
- Environmental precautions:

 $\textbf{Cautions:} \ \text{Keep spills \& cleaning runoff out of municipal sewers \& open bodies of water.}$

Methods for cleaning up:

Contain spills immediately with inert materials (e.g., sand, earth)

Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

Section - 7

Handling and Storage

Handling.

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

- Further information on storage conditions: Keep from freezing product stability may be affected. STIR WELL BEFORE USE.
- **Storage:** Storage temperature: 10 40°C
- Other data: Vapors can be evolved during processing operations.

Seaton - 8

Exposure Controls / Personal Protection

- Exposure limit (S): Exposure limits are listed below, if they exist.
- Exposure controls
- **Eye protection:** Safety glasses with side-shields. Eye protection worn must be compatible with respiratory Protection system employed.
- **Hand protection:** The gloves listed below may provide protection against permeation. (Gloves of other Chemically resistant materials may not provide adequate protection): neoprene gloves.
- **Respiratory protection:** Use certified respiratory protection equipment meeting EU requirements (89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures methods or procedures of work organization.
- Protective measures: Facilities storing or utilizing this material should be equipped with first aid facility.
- **Engineering measures:** Use only in area provided with appropriate exhaust ventilation.

Seaffon-9

Physical and Chemical Properties

Physical state Thick Paste Colour **Base Colour** Odour Ammonical рΗ 8.0 - 9.0Boiling point / range 100°C Water Melting point / range 0°C Water Flash point Noncombustible Lower explosion limit not applicable Upper explosion limit not applicable

Vapour pressure - 22.6648 Pa at 20°C. Water

Relative vapour density - <1.0 Water Water solubility - Dilutable Relative density - 1.85 ± 0.05

Viscosity, dynamic - PR at $300C - 355 \pm 5$ Units

Evaporation rate - <1.00 Water Percent volatility - 18.0 % Water

NOTE: The physical data presented above are typical values and should not be construed

Seation-10

Stability And Reactivity

Hazardous reactions: Not known.

Materials to avoid: There are no known materials which are incompatible with this product.

Seatlon-11

Toxicological Information

No data are available for this material. The information shown is based on profiles of compositionally similar materials.

Acute oral toxicity: LD50 rat > 5,000 mg/kg
Acute dermal toxicity: LD50 rabbit > 5000 mg/kg
Skin irritation: rabbit May cause transient irritation

Eye irritation: rabbit No eye irritation

Seation - 12

Ecological Information

No experimental data of the product available.

Section - 13

Disposal Consideration

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water. **Disposal:** For Disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal Regulations.

Section - 14

Transport Information

Classification for ROAD and Rail transport: Not Regulated (Not dangerous for transport)

Classification for SEA transport: Not Regulated (Not dangerous for transport) **Classification for AIR transport:** Not Regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country Variations in regulations.

Section - 15

Regulatory Information

Label: Classification and labeling have been performed according to regulations.

Seatlon-16

Other Information

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
Bac	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average
I	Bar denotes a revision from prior MSDS

The information provided in this Safety Data Sheet is correct to the best our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.